

# REMS Akku-Cat ANC VE

Cordless universal reciprocating saw

Powerful, robust, handy power tool for universal free-hand sawing. Only 3.1 kg. Ideal for assembly, dismantling, repair.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Especially also for steel pipes

**REMS Akku-Cat ANC VE Li-Ion – saws anything, anywhere. Extremely versatile and powerful. Robust and handy.**

## Universal use

Ready for use anywhere, free-hand, overhead, in confined areas, flush to wall. Mains independent. Extremely versatile and efficient, particularly for metal. Saws metal pipes, boilers, tanks, bath tubs, window frames, etc., for rescue and disaster service operations. Also for plunge-cut sawing.

## Design

Robust, job site-proven. Slender, handy design. Super light, drive unit with battery only 3.1 kg. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward. Proven D-shaped handle. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful 18 V battery motor with ample reserve capacity, 500 W output. Safety tip switch. Electronic charging status check with low discharge protection.

## Sturdy, square lift rod

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life.

## Oscillating drive with ANC

Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

## Vario-Electronic

Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 1,800 rpm (acceleration switch).

## Aggressive orbital action

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.

## Li-Ion PLUS technology

Highly resistant Li-Ion 18 V battery with 3.2 Ah capacity, for long service life. Powerful and light. Total discharge and overload protection with single cell monitoring. Temperature monitoring during the charging process. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger for short charging times.

## Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

## REMS saw blades

See page 64–65.



German Quality Product



3.5 kg	500 W	18 V	VE
ANC			

## Supply format

**REMS Akku-Cat ANC VE Li-Ion.** Battery driven universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing. Drive unit with D-shaped handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful 18 V battery motor, safety tip switch. Electronic stepless speed control (acceleration switch) 0 to 1,800 rpm. Battery Li-Ion 18 V, 3.2 Ah, rapid charger Li-Ion/Ni-Cd 230 V or 110 V, 50–60 Hz, 50 W. Universal saw blade clamp. Hexagon key. 1 pcs REMS universal saw blade 150-1,8/2,5. In sturdy case.

	Art.-No.	
	560051	

Other voltages on request.

## Accessories

Description	Art.-No.
<b>REMS saw blades</b> see page 64–65.	
<b>REMS Akku-Cat ANC VE drive unit, without battery</b>	560009
<b>Battery Li-Ion 18 V, 3.2 Ah</b>	565225
<b>Rapid charger Li-Ion/Ni-Cd 230 V, 50–60 Hz, 65 W</b>	571560
<b>Case with inlay</b>	566025

