

REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

| Thread type | Size | Art.-No. |
|---|------------|----------|
| Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT) | R 1/8 | 521000 |
| | R 1/4 | 521010 |
| | R 3/8 | 521020 |
| | R 1/2 | 521030 |
| | R 3/4 | 521040 |
| | R 1 | 521050 |
| | R 1 1/4 | 521060 |
| | R 1 1/2 | 521070 |
| | R 2 | 521080 |
| Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT) | R 1/8 LH | 521100 |
| | R 1/4 LH | 521110 |
| | R 3/8 LH | 521120 |
| | R 1/2 LH | 521130 |
| | R 3/4 LH | 521140 |
| | R 1 LH | 521150 |
| | R 1 1/4 LH | 521160 |
| | R 1 1/2 LH | 521170 |
| | R 2 LH | 521180 |
| Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1 | NPT 1/8 | 521200 |
| | NPT 1/4 | 521210 |
| | NPT 3/8 | 521220 |
| | NPT 1/2 | 521230 |
| | NPT 3/4 | 521240 |
| | NPT 1 | 521250 |
| | NPT 1 1/4 | 521260 |
| | NPT 1 1/2 | 521270 |
| | NPT 2 | 521280 |
| Threads M for electric conduit EN 60423 | M 16 x 1.5 | 521300 |
| | M 20 x 1.5 | 521310 |
| | M 25 x 1.5 | 521320 |
| | M 32 x 1.5 | 521330 |
| | M 40 x 1.5 | 521340 |
| | M 50 x 1.5 | 521350 |



Right-hand pipe thread



Left-hand pipe thread



German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

| Thread type | Size | Art.-No. |
|---|------------|----------|
| Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT) | R 1/8 | 521002 |
| | R 1/4 | 521012 |
| | R 3/8 | 521022 |
| | R 1/2 | 521032 |
| | R 3/4 | 521042 |
| | R 1 | 521052 |
| | R 1 1/4 | 521062 |
| | R 1 1/2 | 521072 |
| | R 2 | 521082 |
| Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT) | R 1/8 LH | 521102 |
| | R 1/4 LH | 521112 |
| | R 3/8 LH | 521122 |
| | R 1/2 LH | 521132 |
| | R 3/4 LH | 521142 |
| | R 1 LH | 521152 |
| | R 1 1/4 LH | 521162 |
| | R 1 1/2 LH | 521172 |
| | R 2 LH | 521182 |
| Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1 | NPT 1/8 | 521202 |
| | NPT 1/4 | 521212 |
| | NPT 3/8 | 521222 |
| | NPT 1/2 | 521232 |
| | NPT 3/4 | 521242 |
| | NPT 1 | 521252 |
| | NPT 1 1/4 | 521262 |
| | NPT 1 1/2 | 521272 |
| | NPT 2 | 521282 |
| Threads M for electric conduit EN 60423 | M 16 x 1.5 | 521302 |
| | M 20 x 1.5 | 521312 |
| | M 25 x 1.5 | 521322 |
| | M 32 x 1.5 | 521332 |
| | M 40 x 1.5 | 521342 |
| | M 50 x 1.5 | 521352 |



German Quality Product